

FEATURES

- Low Cost
- 90-264Vac Universal Input
- CISPR'B' & CNS'B' Compliance
- 100% Burn-In Test
- Over Voltage Protection Installation
- Short-Circuit Protection Installation
- Protection Type: Auto-Recovery




SPECIFICATION

Model	SP9926
Item	
Input Voltage	AC 90~264V
Input Frequency	47~63Hz
Efficiency	70% Typical
Operating Temperature	0~50
Storage Temperature	-20~85
Weight	96g
Safety Description	UL, CUL, TUV

(*) : Under Development

(I/P) : In Process

MECHANICAL



Unit: m.m.

OUTPUTS

Model No.		SP9926		
Vo		Vo1	Vo2	Vo3
		+5V	+12V	-12V
Load	Min	0.1A	0.04A	0A
	Rated	1A	0.2A	0.1A
	Surge	---	---	---
Regulation	Line	1%	1%	1%
	Load	3%	5%	10%
Tolerance		+/-4%	+/-5%	+/-10%
Ripple & Noise		50mV	120mV	120mV

Ref. No.	Connector Type	Mating Connector Type
CN1	TKP P-8800I or Equivalent	TKP H8800 or Equivalent
Housing	TKP H8800 or Equivalent	TKP P-8800I or Equivalent